

|  |                   |                          |
|--|-------------------|--------------------------|
| MODEL  |                   | MPW 2                    |
| Type   |                   | 2 pipes                  |
| Codes - Models with infrared remote control    |                   | MPW2B5X                  |
| Codes - Models without infrared remote control |                   | MPW2B5B                  |
| Cooling capacity                               | Units             |                          |
| Total cooling capacity 7/12°C (LS/MS/HS)(1)    | kW                | 0,96/-/1,60              |
| Sensible cooling capacity 7/12°C (LS/MS/HS)(1) | kW                | 0,74/-/1,30              |
| Heating capacity                               |                   |                          |
| Heating capacity 50° C (LS/MS/HS) (2)          | kW                | 1,49/-/2,10              |
| Electric heating element                       | kW                | -                        |
| Air flow rate (LS/MS/HS)                       | m <sup>3</sup> /h | 180/-/270                |
| Circuit specifications and connections         |                   |                          |
| Water flow rate at maximum power in cooling    | m <sup>3</sup> /h | 0,29                     |
| Pressure drop at maximum power in cooling (3)  | kPa               | 27                       |
| Pressure drop at maximum power in heating (3)  | kPa               | 25                       |
| Hidraulic connection                           |                   | 1/2" F - GAZ             |
| Condensate discharge                           |                   | Outer diameter end 18 mm |
| Electrical specifications                      |                   |                          |
| Power 50 Hz                                    |                   | 230/1                    |
| Maximum power consumption                      | W                 | 24                       |
| Running noise                                  |                   |                          |
| Sound power per EN12102 (LS/MS/HS)             | dB(A)             | 35/-/45                  |
| Sound pressure level at 2 m (LS/MS/HS)         | dB(A)             | 26/-/36                  |
| Operating range                                |                   |                          |
| Operating range water temperature              | °C                | +4°C / +60°C             |

1) Indoor temperature in cooling: +27°C D.B./ + 19°C W.B.

2) Indoor temperature in heating: +20°C.

3) Pressure drop for water without glycol.