


# 402EA

Nimi: **Pistorasia**  
 Pistorasia, Jussi, 2-osainen, maadoitettu, jousiliittimet  
 Jussi

Tyyppi: 402EA  
 EAN: 6418677335815  
 Snro: 2406578

Kuvaus: Pistorasiassa on liittimet kutakin kosketinta kohden ja niihin voi kytkeä max 4 johtoa (haaroitusmahdollisuus). Liittimet on hyväksytty ML ja MK johtimille. Ei potentiaalivapaita liittimiä. Lapsisuoja on integroitu pistorasian runkoon. IP21 tiiveys saavutetaan vain jos kaapeli tuodaan alhaalta.

Pakkaus: 10/100  
 Yksikkö: KPL



## Tekniset tiedot

### Luokat

Kotelointiluokka IP21

### Sähkösuureet

Nimellisvirta 16 A  
 Nimellisjännite 250 V

### ETIM

ETIM 7 EC000125 (EC000125)

ETIM 8 EC000125 (EC000125)

### ETIM 7

Model Protective contact (SCHUKO)  
 Protective contact yes  
 Protective earth pin round no  
 Number of active Pins (round)  
 Number of active Pins (flat)  
 With signal lamp no  
 With built-in USB power supply no  
 Number of units 2  
 Number of modules (module system) 1  
 Number of socket outlets switchable  
 Number of phases 1

# 402EA

| Imprint/indication                            | Without imprint           |
|---|---------------------------|
| Connection type                               | Plug clamp                |
| With hinged lid                               | no                        |
| With child-protection                         | yes                       |
| Label space/information surface               | no                        |
| Colour  | White                     |
| RAL-number (akin)                             | 9010                      |
| Transparent                                   | no                        |
| Lockable                                      | no                        |
| Eject-mechanism                               | no                        |
| Insulated mounting                            | no                        |
| With function lighting                        | no                        |
| With orientation lighting                     | no                        |
| Over voltage protection                       | no                        |
| Fault current protection                      | no                        |
| With miniature fuse                           | no                        |
| Special power supply                          | No special power supply   |
| Mounting method                               | Surface mounted (plaster) |
| Type of fastening                             | Mounting with screw       |
| Material                                      | Plastic                   |
| Material quality                              | Thermoplastic             |
| Halogen free                                  | yes                       |
| Surface protection                            | Untreated                 |
| Surface finishing                             | Matt                      |
| Antibacterial treatment                       | no                        |
| With on/off switch                            | no                        |
| With loop through function                    | no                        |
| Rotated central insert                        | no                        |
| Nominal current                               | 16 A                      |
| Nominal voltage                               | 250 V                     |
| Frequency                                     | 50 Hz                     |
| Suitable for degree of protection (IP)        | IP21                      |
| For heavy conditions (in accordance with VDE) | no                        |
| Width of device                               | 65 mm                     |
| Height of device                              | 98 mm                     |
| Depth of device                               | 43 mm                     |